



CURRENT TRANSFORMERS

Model 19 (Window Size: 4.25" Diameter)

Catalog Number	Current Ratio	VA for ±1% Class	ANSI Metering Class at 60 Hz.					Secondary Winding Resistance Ω at 75°C	Continuous Thermal Rating Factor	
			B0.1	B0.2	B0.5	B0.9	B1.8		at 30°C	at 55°C
19 **—301	300:5	4.0	0.6	0.6	2.4	2.4	4.8	0.048	2.0	2.0
19 **—401	400:5	10.0	0.3	0.3	1.2	2.4	2.4	0.064	2.0	2.0
19 **—501	500:5	15.0	0.3	0.3	0.6	1.2	2.4	0.087	2.0	1.5
19 **—601	600:5	15.0	0.3	0.3	0.6	1.2	1.2	0.116	2.0	1.5
19 **—751	750:5	25.0	0.3	0.3	0.3	0.6	1.2	0.145	1.5	1.33
19 **—801	800:5	30.0	0.3	0.3	0.3	0.6	1.2	0.155	1.5	1.33
19 **—102	1000:5	30.0	0.3	0.3	0.3	0.6	1.2	0.242	1.33	1.0
19 **—122	1200:5	40.0	0.3	0.3	0.3	0.3	0.6	0.291	1.33	1.0
19 **—152	1500:5	15.0	0.3	0.3	0.6	0.6	0.6	0.200	1.5	1.0
19 **—162	1600:5	15.0	0.3	0.3	0.3	0.6	0.6	0.213	1.5	1.0
19 **—202	2000:5	20.0	0.3	0.3	0.3	0.3	0.6	0.266	1.33	1.0
19 **—252	2500:5	20.0	0.3	0.3	0.3	0.3	0.3	0.333	1.0	0.8
19 **—302	3000:5	25.0	0.3	0.3	0.3	0.3	0.3	0.399	1.0	0.8

** Note When Ordering use prefix below to indicate unit designation/configuration. (i.e. 19SHT-301)

*SHT= Square Case w/o molded feet and terminals

*SHL= Square Case w/o molded feet and 24" leads

RL= Thin Round Case and 24" leads



Model 19 (Window Size: 4.25" Diameter)

