



CURRENT TRANSFORMERS

Model 7 (Window Size: 2.50" Diameter)

Catalog Number	Current Ratio	Accuracy at 60 Hz	Burden VA at 60Hz
7 **--101	100:5	± 2%	2.5
7 **--151	150:5	± 1%	5.0
7 **--201	200:5	± 1%	5.0
7 **--251	250:5	± 1%	5.0
7 **--301	300:5	± 1%	12.5
7 **--401	400:5	± 1%	15.0
7 **--501	500:5	± 1%	25.0
7 **--601	600:5	± 1%	30.0
7 **--751	750:5	± 1%	30.0
7 **--801	800:5	± 1%	35.0
7 **--102	1000:5	± 1%	35.0
7 **--122	1200:5	± 1%	35.0
7 **--152	1500:5	± 1%	40.0
7 **--162	1600:5	± 1%	45.0

****Note:** When ordering, use prefix below to indicate unit designation/configuration.
(i.e. 7SFT-101)

SFT= Square Case w/molded feet and terminals

SFL= Square Case w/molded feet and 24" leads

*SHT= Square Case w/o molded feet and terminals

*SHL= Square Case w/o molded feet and 24" leads

RL= Thin Round Case and 24" leads

DRL= Thick Round Case and 24" leads

*Note-Mounting Brackets for the 7SHT and 7SHL Part Number 1121A00021-1