

## TOROIDAL CURRENT TRANSFORMERS

### Model 192 Ratio to 5 (Window Size: 1.75" Dia.)

**Application:** Used with ammeters, watt meters and cross current compensation.

**Frequency:** 50-400 Hz

**Insulation Level:** 600 Volts, 10kV BIL Full Wave

**Standards:** CSA 66.1-06, CSA 66.2-06, IEEE C 57.13, and UL 506

- Flexible leads available for all case configurations. Flexible leads are UL 1015 105°C, C.S.A approved #16 AWG, 24" long standard length. Non-standard lengths are available upon request.
- Terminals are brass studs No. 8-32 UNC with one flat washer, one lock washer and one nut each. Terminals are only available on the square case configuration.
- Mounting brackets kits available when required.
- Approximate weight: 4.75 lbs.



Catalog Number	Current Ratio	Relay Class	ANSI Metering Class at 60 Hz					Secondary Winding Resistance ( $\Omega$ @ 75°C)	Continuous Thermal Rating Factor	
			B0.1	B0.2	B0.5	B0.9	B1.8		@ 30°C	@ 55°C
192-101	100:5	-	0.6	1.2	2.4	4.8	-	0.031	2.00	2.00
192-151	150:5	-	0.6	0.6	1.2	2.4	4.8	0.058	2.00	2.00
192-201	200:5	C10	0.3	0.3	0.6	1.2	2.4	0.063	2.00	1.50
192-251	250:5	C10	0.3	0.3	0.3	0.6	1.2	0.097	2.00	1.50
192-301	300:5	C10	0.3	0.3	0.3	0.6	1.2	0.131	2.00	1.33
192-401	400:5	C20	0.3	0.3	0.3	0.3	0.6	0.174	1.50	1.00
192-501	500:5	C20	0.3	0.3	0.3	0.3	0.6	0.218	1.50	1.00

**TOROIDAL CURRENT TRANSFORMERS**  
 Model 192 Ratio to 5 (Window Size: 1.75" Dia.)

